

IN THE SPECIFICATION:

Please replace paragraph 1 at page 30, with the following rewritten paragraph:

Then, the process goes to Step S2 where if the attendee in the conference opens the control screen 50c for allowing the attendee in the conference to operate the creator 5, only the client becomes the client PC for recorder (~~see FIG. 6~~ see FIG. 7). On GUI screen 50 of the notebook personal computer PCi, the icon K1 of the creator 5, shown in FIG. 6, is right-clicked and an item, "control" is selected from the displayed menu, the control screen 50c is displayed.

Please replace paragraph 1 at page 43, with the following rewritten paragraph:

In this example, as compared with the image indicating the rocket in Picture 3, the mouse-operating right concerning the image indicating the sun in Picture 1 is previously obtained, so that the enlarged image indicating the sun in Picture 1 may be displayed on the right upper portion of the contents-editing screen 50g. Concerning the image indicating the rocket in Picture 3, when the display frame 15 is further moved in a right way so that the image indicating the sun in Picture 1 fades out of the display frame 15, a display on the right upper portion of the contents-editing screen 50g is changed from the image indicating the sun in Picture 1 to the image indicating the rocket in Picture 3 to display the enlarged image indicating the ~~sun~~ (Projector 1) rocket (Projector 3).

Please replace paragraph 1 at page 44, with the following rewritten paragraph:

The access point 6 is arranged as shown in ~~FIG. 17~~ FIG. 13 so that the three notebook personal computers PCi and the three communicators ~~2A through 2C~~ 3A through 3C are organized as wireless LAN configuration. The creator 5 and the three communicators ~~2A through 2C~~ 3A through 3C are connected with each other using HUBS 9C through 9E and the communication cable 40. Electronic equipment for network configuration such as the notebook

personal computers PCi, the creator 5, the projectors 2A through 2C, and the communicators 3A through 3C, is powered on. The notebook personal computer PCi of the presenter of materials is then set as the client PC.

Please replace paragraph 4 at page 48 continuing onto page 49, with the following rewritten paragraph:

In this embodiment, a case where the three communicators ~~3A, 3B~~ 3A through 3C are used has been described, but the invention is not limited to such the case and thus, if such a configuration that one communicator is connected with plural projectors 2A through 2C and the like is taken, similar processing can be made by transferring the contents DIN of displayed subject and the target image flag FG to each of the control blocks in display device.